

QuietGlue® Pro

Acoustical Glue




The High Performing, Low Cost Noise Reducing Glue

QuietGlue® Pro is a high performance, low cost acoustical compound designed to be cost effective for commercial projects and small do-it-yourself projects.


QuietGlue® Pro Benefits:

- Easy to use
- Ideal for use with virtually any kind of wood or drywall
- Does not require special training
- Low VOC, water-based compound, solvent-free
- Lab tested in accordance with ASTM D3273 and E90

STOP THE NOISE IN 2 EASY STEPS



1 Dispense Glue



2 Screw onto wall

Product Specifications:

| | |
|--------------------------|--|
| Model: | QuietGlue® Pro |
| Color: | Yellow |
| Density: | 1,030 kg/m |
| Solid content: | >70 wt % |
| Viscosity: | 400,000 - 800,000 centipoise |
| Drying time: | 24-48 hours |
| Coverage: | 32 ft ² /tube; 146 ft ² /gallon |
| Storage temp: | 40° F - 100° F (Do Not Freeze) |
| Working time: | 1-2 hours |
| Available sizes*: | 28-oz tube, 1-gal pail, 5-gal pail, case of 12 28-oz tubes |

Note: Tubes require a standard caulking gun. A bulk caulking gun is recommended for use with 1 gallon and 5 gallon buckets. Application of excess glue will not improve sound damping and can potentially cause seepage of excess glue along the edges.

Visit www.QuietRock.com for installation instructions and complete documentation.